

## RUGGED FLOOR SAW FOR TOUGHEST CONSTRUCTION SITE USE

- Torsion resistant frame design with a low center of gravity
- Long wheelbase distance for high lateral stability
- The smooth stub axle steering system allows for cutting corrections without physical strain, and for quick and easy set-up and/or moving of the floor saw
- Quiet, water-cooled HATZ 4-Zylinder turbodiesel engine
- The shift gearbox grants an easy adjustment of the 3 different rpm speeds
- Large v-belt drive
- Large saw blade shaft bearings with special seals for longer life span.
- The air intake is on the operator's side, which means only clean air is taken in.
- Gentle, easy to control start-up of feed speed due to hydrostat and low-maintenance chainless gear box
- Feedcrank including an operation switch on both sides for lift and lower allows single-hand operation
- Electro hydraulic saw blade lift



MULTICUT 900  
Picture incl. blade guard

### Basic version MULTICUT 900 SG:

Shift gearbox with 3 different rpm speeds – 950, 1620 and 2450 1/min, gearbox (clockwise/counter-clockwise rotation and neutral position), flange spraying system

### Basic version MULTICUT 900 SGH:

Shift gearbox with 3 different rpm speeds – 950, 1620 and 2450 1/min, gearbox (clockwise/counter-clockwise rotation and neutral position), flange spraying system, hydraulic interface for suction unit: closed system – suction unit is directly driven by a hydraulic interface to the floor saw



[ 1 ] Blade guard incl. vacuum shoe



[ 2 ] Spot-light



[ 3 ] Warning flasher

TECHNICAL DATA	MULTICUT 900 SG	MULTICUT 900 SGH
cutting depth max.	515 mm	515 mm
cutting depth setting	electro hydraulic with depth gauge	electro hydraulic with depth gauge
saw blade Ø max.	1200 mm	1200 mm
saw blade flange	25,4 or 35 mm (6 x M12 - TK120 mm)	
traction drive forward	hydrostatic stepless 0-50 m/min	hydrostatic stepless 0-50 m/min
traction drive reverse	hydrostatic stepless 0-25 m/min	hydrostatic stepless 0-25 m/min
drive motor	HATZ diesel 4-cylinder	HATZ Diesel 4-Zylinder
output power max.	55 kW, 74,8 hp	55 kW, 74,8 hp
saw blade speed	950 / 1620 / 2450 1/min.	950 / 1620 / 2450 1/min.
dimensions (L/W/H)	1580/1050/1690 mm	1580/1050/1690 mm
weight	1150 kg	1200 kg
left/right cut	yes	yes

#### DIAMOND TOOLS RECOMMENDATION

Asphalt	ASP 703
Concrete	BSP 501

FLOOR SAWS	NR.
MULTICUT 900 SG 25,4 without diamond blade, without blade guard	1040904
MULTICUT 900 SGH 25,4 without diamond blade, without blade guard	1040905
MULTICUT 900 SG 35 without diamond blade, without blade guard	1040254
MULTICUT 900 SGH 35 without diamond blade, without blade guard	1040255

ACCESSORIES	NR.
MULTICUT 900 SG / SGH - vacuum unit VACUUM-WET 100 P	818167
MULTICUT 900 SG / SGH - vacuum unit VACUUM-WET 300	818203
MULTICUT 900 SG / SGH - blade guard 800 mm	1031207
MULTICUT 900 SG / SGH - blade guard 1000 mm	1031208
MULTICUT 900 SG / SGH - blade guard 1200 mm	1031209
[ 1 ] MULTICUT 900 SG / SGH - blade guard 500 mm incl. vacuum shoe	1004709
[ 1 ] MULTICUT 900 SG / SGH - blade guard 800 mm incl. vacuum shoe	816187
[ 2 ] MULTICUT 900 SG / SGH - spot-light LED 12 V	1040256
[ 3 ] MULTICUT 900 SG / SGH - warning flasher	816002
MULTICUT 900 SG / SGH - seat	1040906
MULTICUT 900 SG / SGH - water pump set incl. water filter	813046
MULTICUT 900 SG / SGH - adapter kit - shaft 25,4 mm for 6-hole flange	1018697
MULTICUT 900 SG / SGH - diesel particulate filter incl. mounting	1016063
MULTICUT 900 SG / SGH - individual color	910050