



Linija za komprimirani zrak s vijčanim kompresorima

CompAir L37 RS i CompAir L30e

Vijčani kompresor

CompAir L37 RS

- Frekventno reguliran
- Mikroprocesorsko upravljanje
dodirom DELCOS XL

Kapacitet

kod 5 bar min-max.....	1,51 – 6,90 m ³ /min
kod 6 bar min-max.....	1,50 – 6,88 m ³ /min
kod 7 bar min-max.....	1,48 – 6,86 m ³ /min
kod 8 bar min-max.....	1,46 – 6,66 m ³ /min
kod 9 bar min-max.....	1,44 – 6,36 m ³ /min
kod 10 bar min-max.....	1,41 – 6,06 m ³ /min
kod 11 bar min-max.....	1,80 – 5,78 m ³ /min
kod 12 bar min-max.....	2,19 – 5,52 m ³ /min
kod 13 bar min-max.....	2,58 – 5,27 m ³ /min

Motor.....	IE3, 37 kW / 400 V / 50 Hz
Klasa zaštite.....	IP 55
Broj okretaja.....	800 – 3.600 °/min
Temperatura okoline min / max. 1 do 45° C	
Nivo buke.....	67 db(A)
Težina.....	948 kg

Vijčani kompresori

CompAir L30e

Kapacitet	5,91 m ³ /min
Tlak.....	7,5 bar
Motor.....	IE3, 30 kW / 400 V / 50 Hz
Klasa zaštite.....	IP 55

Sušači zraka

CompAir F80S

Kapacitet sušača.....	8,03 m ³ /min
Točka rosišta.....	+ 3 °C

CompAir F62S

Kapacitet sušača.....	6,20 m ³ /min
Točka rosišta.....	+ 3 °C



HEP d.o.o. Zagreb