

# COMPACTCUT 200

**LISSMAC**  
CONSTRUCTION TECHNOLOGY

IDEALLY SUITED FOR SMALL AND MEDIUM SIZED REPAIR WORKS  
IN ASPHALT AND CONCRETE

- Floor saw in robust and compact construction
- Closed and solid frame
- The smooth raising and lowering of the saw blade with a closed threaded spindle prevents damaging of the saw blade
- Adjustable cutting depth indicator for all saw blade diameters
- A large 33l capacity water tank reduces work interruptions
- The water cooling system provides an optimum saw blade cooling, this guarantees a longer saw blade life
- Easy detachable saw blade cover
- Simple service operations - good access to engine and cutting shaft
- With a parking brake



COMPACTCUT 200 P



[ 1 ] COMPACTCUT 200 D



Threaded spindle with depth gauge



Incl. water tank



TECHNICAL DATA	COMPACTCUT 200 P	COMPACTCUT 200 D
cutting depth	180 mm	180 mm
cutting depth setting	stepless threaded spindle with depth gauge	
saw blade Ø max.	500 mm	500 mm
saw blade holder	25.4 mm	25.4 mm
drive motor	Honda petrol 1-cylinder	HATZ diesel 1-cylinder
output power max.	8.7 kW, 11.8 hp	4.6 kW, 6.3 hp
saw blade speed	2500 1/min.	2500 1/min.
dimensions (L/W/H)	1120/550/1060 mm	1120/550/1060 mm
weight	116 kg	126 kg

#### DIAMOND TOOLS RECOMMENDATION

Asphalt	ASW 10
Concrete	BSW 10

<b>FLOOR SAWS</b>	<b>NR.</b>
COMPACTCUT 200 P without diamond blade, incl. blade guard 500 mm	1017015
[ 1 ] COMPACTCUT 200 D without diamond blade, incl. blade guard 500 mm	1017016
<b>ACCESSORIES</b>	<b>NR.</b>
COMPACTCUT 200 - individual color	910050