

COMPACTCUT 701 E

LISSMAC
CONSTRUCTION TECHNOLOGY

POWERFUL AND COMPACT ELECTRO JOINT CUTTER
IN DEMANDING BUILDING CONDITIONS

- The lowering and raising of the saw blade is infinitely variable, damage to the saw blade is thus prevented
- extremely powerful electro-seam cutter with 30 kW drive motor
- Clear and ergonomic design of controls.
- Saw hood foldable at the front for overcuts
- The 3-speed manual gearbox enables optimum tuning of the speed of the cutting shaft according to the sheet size used
- The feed of the machine is smooth over a hydrostatic drive



TECHNICAL DATA	COMPACTCUT 701 E
cutting depth max.	431 mm
cutting depth setting	electro hydraulic
saw blade Ø max.	1000 mm
saw blade holder	25.4 mm
feed/drive unit	max.60 m/min
cutting gear	max.60 m/min
drive motor	electric
output power max.	30 kW / 400 V / 63 A
saw blade speed	L 840 1'/min, M 1240 1'/min, H 1960 1'/min.
left and right cut	yes
dimensions (L/W/H)	1900/840/1100 mm
weight	700 kg

DIAMOND TOOLS RECOMMENDATION

Asphalt	ASW 11
Concrete	BSP 301

FLOOR SAW	NR.
COMPACTCUT 701 E without diamond blade, incl. blade guard 1000 mm	1059230
ACCESSORIES	NR.
COMPACTCUT 701 E - further blade guards on demand	-