COMPACTCUT 905 P/T



POWERFUL AND COMPACT FLOOR CUTTER FOR DRY CUTTING

- No water required, cleaner surfaces, no further steps needed to prepare joints for grouting.
- Suited for fast preparation of joints, renovations and tight construction sites
- Electro- hydraulic lowering and raising of the saw blade with a threaded spindle with cutting depth indicator prevents damage to the saw blade
- Propulsion by hydrostatic gear drive guarantees smooth and controlled operation of the machine
- Smooth axle pivot steering for quick and easy moving and set-up without physical stress for the operator, as well as effortless cutting adjustments
- · Torsion -resistant frame construction
- Optimal drive unit location allows for easy access for routine maintenance work (air filter, battery, oil and fuel filter)
- · Parking brake and neutral gear comes as a standard feature
- · Low center of gravity ensures a precise saw cut
- $\cdot\;$ Suitable for angle cuts of 5°, which allows for flush wall and curb cuts
- · Rugged V-ribbed belt for optimal power transmission



LISSMAC COMPACTCUT 905



TECHNICAL DATA	COMPACTCUT 905 P/T
cutting depth max.	100 mm
cutting depth setting	hydraulic with lowering valve
saw blade dia. max.	350 mm
saw blade bore hole	25.4 mm
motor	Briggs+Stratton petrol 2 cyl.
output max.	26 kW, 35 hp
saw blade speed	2375 ¹ /min.
dimensions (L/W/H)	1250/600/1300 mm
weight	345 kg

DIAMOND TOOLS RECOMMENDATION

Asphalt

ASTP 703

Subject to technical change without notice LISSMAC / 03.2018

FLOOR SAWS	
COMPACTCUT 905 P/T without diamond blade, incl. blade guard 350 mm	

LISSMAC Maschinenbau GmbH · Lanzstraße 4 · D-88410 Bad Wurzach · Tel. +49 7564 307-0 · Fax -500 · lissmac@lissmac.com · www.lissmac.com

NR. 1026938

.....