

POWERFUL AND COMPACT FLOOR SAWS IN THE MIDDLE CLASS

- Particularly compact construction
- The hand cranked travel enables a uniform cutting rate, guaranteeing a straight saw cut, thereby extending the life of the saw blade – lower cutting costs
- The FS 20 is also available with electric power travel, ideally suited to heavy cutting in concrete or asphalt.
- For longer service life the vertically positioned engine guarantees permanent oil supply in every cutting situation
- Lowering and raising the saw blade is done smoothly, therefore preventing damage to the saw blade
- · Clear and ergonomic arrangement of the instruments
- · Saw hood front can be raised for intersections
- The rear running wheel sits outside of the saw cut this makes recutting of cut joints easy
- The LISSMAC swivel arm principle saves time and money long times for converting from left to right cut are eliminated by the 180 degree swivel saw arm
- · Large water and fuel tanks reduce down-time to a minimum.
- Parking brake, water saving flange spraying and saw cutting depth indicator are standard equipment








[2] Blade guard incl. vacuum shoe







TECHNICAL DATA	FS 20 B (-VE)	FS 20 D (-VE)		
cut depth	220 mm	220 mm		
cutting depth setting	stepless threaded spindle v	stepless threaded spindle with depth gauge		
saw blade Ø max.	600 mm	600 mm		
saw blade holder	25.4 mm	25,4 mm		
drive motor	Honda petrol V2-cyl.	HATZ Diesel		
output power max.	15.5 kW/20.8 hp	10.1 kW/13.7 hp		
saw blade speed	1920 ¹ /min.	1920 ¹ /min.		
dimensions (L/W/H)	1100/750/1100 mm	1100 /750 /1100 mm		
weight	205 kg	263 kg		
weight VE	210 kg	268 kg		
left/right cut	yes	yes		
feed standard	hand crank	hand crank		
feed FS 20-VE	electric/hand crank	electric/hand crank		

.....

DIAMOND TOOLS RECOMMENDATION

A	Asphalt	ASW 10	
C	Concrete	BSW 10	

FLOOR SAWS	NR.
[1] FS 20 B without diamond blade, incl. blade guard 600 mm	815034
FS 20 B/VE without diamond blade, incl. blade guard 600 mm	815035
FS 20 D without diamond blade, incl. blade guard 600 mm	815011
FS 20 D/VE without diamond blade, incl. blade guard 600 mm	815014
ACCESSORIES	NR.
[2] FS 20 - blade guard 500 mm incl. vacuum shoe	816136
FS 20 - individual color	010050

LISSMAC Maschinenbau GmbH · Lanzstraße 4 · D-88410 Bad Wurzach · Tel. +49 7564 307-0 · Fax -500 · lissmac@lissmac.com · www.lissmac.com