UNICUT 600



FULLY HYDRAULIC PRECISION FLOOR SAW FOR PROFESSIONAL USE

- · Multifunctional joystick for ease of operation
- Electro hydraulic steering system optimal hydraulic cycle for improved saw blade power transmission
- Drive motor and saw blade speed are electro-hydraulically controlled for ideal saw blade cutting speed on various applications
- · Optimal weight distribution due to low center of gravity
- · Large fuel tank for reduced downtime
- Quick changeover from left to right-hand cutting can be pivoted by 180°
- · Large, non-marking drive wheels
- Stepless hydraulic height adjustment of the blade guard, independent of saw motor.
- Slanted cuts from inside to outside or vice versa, up to 15 degrees
- Motorhousing with saw blade mount can be moved sideways by 100 or 200 mm, as well as up and down by 150 mm.
- Compact and user friendly design, suitable for pushed as well as pulled cuts, adjustable seating position.
- All settings are controlled via the display on the centrally located operating panel, which also displays the engine parameters.
- Easy access for routine maintenance work (air filter, battery, oil and fuel filter).
- UNICUT 600 complies with current emission regulations US EPA Tier 4/EU Stage IV





[1] VACUUM-WET 500



[2] Blade guard incl. vacuum shoe



[3] Remote control



[4] Spot-light



[6] Drill unit

[7] Tandem longitudinal cutting unit

[8] Grooving unit

[5] Warning flasher

TECHNICAL DATA	UNICUT 600
cutting depth max.	630 mm
saw blade Ø max.	1500 mm
saw blade holder	35 mm (6 x M12 - TK120 mm)
traction drive forward	hydraulic stepless 0-60 m/min
traction drive reverse	hydraulic stepless 0-60 m/min
drive motor	DEUTZ turbo diesel 4-cylinder
output power max.	100 kW / 136 hp
emission level	EU Stufe IV/US EPA Tier 4
saw blade speed	600-2800 ¹ /min.
dimensions (L/W/H)	2500/1100/1650 mm
weight	2200 kg
steering	electro-hydraulic
left/right cut	yes

FLOOR SAWS	NR.
UNICUT 600 without diamond blade, without blade guard	1022543
SAW BLADE MOTORS	NR.
variable displacement motor 160 cm³	1018614
variable displacement motor 200 cm³	1005790
ACCESSORIES	NR.
[1] UNICUT 600 - suction unit VACUUM-WET 500	818204
UNICUT 600 - blade guard 800 mm	818079
UNICUT 600 - blade guard 1000 mm	818080
UNICUT 600 - blade guard 1200 mm	818081
[2] UNICUT 600 - blade guard 500 mm incl. vacuum shoe	818153
[2] UNICUT 600 - blade guard 1000 mm incl. vacuum shoe	818083
[2] UNICUT 600 - blade guard 1200 mm incl. vacuum shoe	818072
[2] UNICUT 600 - blade guard 1500 mm incl. vacuum shoe	818162
[3] UNICUT 600 - remote control	1040910
[4] UNICUT 600 - spot-light LED 12 V	1040256
[5] UNICUT 600 - warning flasher	816002
UNICUT 600 - water pump set incl. water filter	813046
[6] UNICUT 600 - drill unit	818208
[7] UNICUT 600 - tandem longitudinal cutting unit	818154
[8] UNICUT 600 - grooving unit and blade guard	-
UNICUT 600 - vacuum shoe for grooving unit	-
UNICUT 600 - seat modification kit for pushed cuts	1018150
UNICUT 600 - diesel particulate filter incl. mounting	1018455
UNICUT 600 - individual color	910050

LISSMAC Maschinenbau GmbH · Lanzstraße 4 · D-88410 Bad Wurzach · Tel. +49 7564 307-0 · Fax -500 · lissmac@lissmac.com · www.lissmac.com